

# TECHNICAL DATA SHEET

**R O S E B U R G**

**AC Sanded Plywood**  
Coquille, OR and Riddle, OR

## Construction Details

**Face:** Douglas Fir

**Core:** Western Softwood

**Centers:** Western Softwood

**Backs:** Western Softwood

- Fully water resistant phenolic resin
- NAUF (No added Urea Formaldehyde)
- Meets APA PS 1-09 standards
- FSC Panels Available

Panel Size	Thickness (inches)	Plys
4' x 8'	1/4, 11/32	3
	15/32, 19/32	5
	23/32	5 or 7 as specified (AC)
	23/32	7 only (AA, AB)
	31/32	7 (AC)
	31/32	9 only (AA,AB)

## Finishing Details

- Finish Sand
- Minor Wood Putty Repair, Occasional Epoxy

## Stamping

- AC: Back Stamp = APA Stamp
- AA/AB: End Stamp = APA Stamp

## Banding and Stencil

- AC: Top Cover - Mark Thickness & Grade
- AA & AB: Top and Bottom Cover - Mark Thickness & Grade
- 3 Bands/3 Stickers

## Packaging Details

Thickness (inches)	Pieces Per Unit	#/MSF	#/Unit
1/4	120	725	2,785
11/32	90	950	2,750
15/32	66	1,350	2,850
19/32	53	1,600	2,715
23/32	44	1,900	2,675
31/32	30	2,700	2,850