

MADE
Tough,
BUILT TO LAST

- Made from real wood
- Easy to paint
- Rich, cedar-grain appearance
- No added urea formaldehyde
- Common groove patterns available
- Safe for children & pets
- Strength & durability
- Dimensional stability
- Plywood inner core
- 50 year limited warranty
- Water resistant
- Clean, veneer wood interior

**50 year
Limited
Warranty**



Overview

Roseburg brings to you the most versatile product in siding for the shed industry.

- Durability; DuraTemp[®] is manufactured with a strong plywood veneer inner core and a tough full 1/8" thick tempered hardboard face that won't split, crack or check — even with rough treatment.
- Strength; DuraTemp is made of genuine plywood, so even though it's lighter, it's also stronger than most siding products.
- Economy; Easy installation and painting means it costs about the same as ordinary siding. Its durability and strength ensure that maintenance costs are kept down.
- Beauty; DuraTemp has a natural cedar-grain textured appearance. Its surface is 100% clear and free of patches and repairs. It is easy to paint, and can withstand exposure to the elements.

Finishing

- Finish as soon as possible after installation
- DuraTemp is available pre-primed with exterior latex primer
- Do not use semi-transparent stain or vinyl acrylic exterior paint
- Apply quality exterior gloss or semi-gloss latex house paint formulated for wood as recommended by your paint supplier

THICKNESS	SPAN RATING	CHANNEL GROOVE	V-GROOVE
3/8"	16" OC	Shallow	Available
15/32"	16" OC	Medium	Available
19/32"	16" OC	Deep	Not Available

Installation

All DuraTemp panels shall be fastened with nonstaining box, siding, or casing nails placed minimum 6" o.c. at the panel edges and 12" o.c. at the intermediate supports. Nails shall be minimum 6d for panels 1/2" and less, and minimum 8d for panels over 1/2". Consult APA for complete installation instructions.

Certifications

- Quality assurance program audited by APA to meet the manufacturing standards
- PS 1 - Meets PS 1 standards for: Veneer grades, glue and bond durability, thickness requirements, testing procedures, finished plywood tolerances, identification and stamping guidelines.

Manufacturing Locations

- Riddle, Oregon

Specifications

Lengths: 7', 8', 9', 10'

Width: 4'

Thicknesses: 15/32", 3/8", 19/32"

Grades: APA & PS 1 Specifications

Face Veneer: Full 1/8" Tempered Hardboard

Core Veneer: Western Softwood

Back Veneer: C grade or better western softwood

Adhesive: NAUF exterior, fully water resistant phenolic glue

Primed: Option

Surface: Textured

Patching: N/A

Edge: Shiplap or Square

Groove Pattern: 4", 8". Groove Depth: Medium, Deep

Span Ratings: 15/32" - 16" o.c., 19/32" 4" & 8" groove - 16" o.c.

Flame Spread Rating: Spread index of 126.2 (allowable 75-200)

Glue Bond Testing: Plywood shall meet the requirements for Exterior bond classification plywood, as defined in the most recent edition of *Voluntary Standard PS1 Structural Plywood*.

Shear Values: DuraTemp siding may be used as wall bracing or shear walls for wind and seismic forces. Consult technical data available from APA.