



HARDWOOD PLYWOOD



TECHNICAL DATA

Lengths	8' & 10'		
Widths	4'		
Core Specifications	Core	Thickness	Plys
	Veneer - Western Softwood Veneer (White Fir), Combination Fiber Core (CFC), Hardwood Cross Band (HXB)	1/4"	3
		3/8", 1/2"	5
		5/8", 3/4"	7
		1", 1-1/8", 1-1/4"	9, 11
Particleboard	1/2", 5/8", 3/4", 1"	3	
MDF	5/32", 3/16", 5.2mm, 1/4", 3/8" 1/2", 5/8" 3/4", 1"	3	
Face Options	<p>Rotary, plain sliced, quarter sliced, rift cut hardwood panels are faced with hand selected hardwood veneers that, when applied to a laminating substrate, create a panel that has the rich beauty of hardwood.</p> <p>RediFinish hardwood panels are produced using a high performance UV cure burnishing sealer and a mar-resistant UV cure topcoat applied to the hardwood veneer face.</p> <p>RediBead Panel combines the look and feel of real wood with a tongue and groove appearance.</p>		
Back Options	Hardwood veneer, Balancing backer		
Finish Options	Natural unfinished, UV-cured clear topcoat, beaded		
Slicing Options	Rotary, Rift Cut, Plain Slicing, Quarter Sawn. Slicing option is based on desired hardwood veneer.		
Veneer Matching Options	Slip, Whole Piece, Pleasing, Book, Random. Natural coloration and arrangement of veneer, comprising the panel face, determine the resulting visual effect. Different matching techniques are used for specific panel applications.		
Dimensional Tolerances	Refer HPVA ANSI/HPVA HP-1-2016		
Resin	ULEF Resin. View Safety Data Sheet on roseburg.com		
Sanding	180-220 grit		
Flame Spread Rating	Class C or Class III		

HARDWOOD PLYWOOD

All Roseburg hardwood panels are produced domestically from the finest hardwood veneer and cores available. The entire product line is third party certified to meet the requirements of EPA TSCA Title VI and is ULEF Exempt. The product can contribute to LEED® v4. SkyPly, RediPly and RediFinish hardwood plywood panels are UL GREENGUARD Certified for low VOC emissions.

COMMON APPLICATIONS

- Cabinetry
- Custom casework
- Fixtures
- Furniture
- Wall panels

STANDARDS & CERTIFICATIONS

- SkyPly is GREENGUARD Certified for low VOC emissions. Refer to certificates on roseburg.com or www.greenguard.org
- Complies with EPA TSCA Title VI and is ULEF Exempt, under Executive Order N-18-038cc, and N-18-038vc



3660 Gateway St, Springfield, OR 97477
800.245.1115 | roseburg.com

Hardwood Plywood
Dillard, OR