

SECTION 1: Identification

1.1. Identification

Product form : Article
Product name(s) : Particleboard, laminated or coated, UltraBlend, SkyBlend, Duramine, Melagard

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Furniture, Cabinetry and Doors

1.3. Supplier

Manufacturer

Roseburg Forest Products
3660 Gateway St.
Springfield, Oregon 97477 - USA
T 541.658.6117 (non-emergency)
<https://www.roseburg.com/>

1.4. Emergency telephone number

In the event of a situation not covered in SECTION 4: First-aid Measures; : **1(800)222-1222**
Available 24/7
Emergency contact : Poison control center

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

The hazards indicated in this document apply only when this product is cut, drilled, or modified in such a way that dust particles are released.

GHS classification

Eye Irrit. 2A
Carc. 1A
Repr. 2
Comb. Dust

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Danger
Hazard statements (GHS) : May form combustible dust concentrations in air
Causes serious eye irritation.
May cause cancer.
Suspected of damaging fertility or the unborn child.
Precautionary statements (GHS) : Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wash hands, forearms and face thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Wood dust, all soft and hard woods	Wood dust, all soft and hard woods Wood dust / Wood dust, all soft and hard woods, except western red cedar / Wood dust, nonallergenic / Wood dust, hard and soft / Wood dust (non-allergenic) / Wood dust, softwoods and hardwoods, except western red cedar / Wood / Wood dusts / Wood dusts (all other species) / Wood dust, all soft and hard woods, except red cedar / WOOD POWDER	CAS-No.: Not applicable	80 - 100
Urea, polymer with formaldehyde and 1,3,5-triazine-2,4,6-triamine	Urea, polymer with formaldehyde and 1,3,5-triazine-2,4,6-triamine UREA/MELAMINE/FORMALDEHYDE RESIN / Urea, polymer with formaldehyde and 1,3,5-triazine-2,4,6-triamine / Formaldehyde-melamine-urea polymer / Melamine-formaldehyde-urea resin / Urea-formaldehyde-melamine polymer / SA-22 / POLYOXYMETHYLENE MELAMINE UREA / Urea-formaldehyde resin modified by polyethylenepolyamine / Urea-melamine-formaldehyde resins / Urea/formaldehyde/melamine copolymer / Polymer of formaldehyde/1,3,5-triazine-2,4,6-triamine/urea	CAS-No.: 25036-13-9	7 - 30
Melamine	Melamine Cyanurotriamide / Cyanurotriamine / 2,4,6-Triamino-1,3,5-triazine / 2,4,6-Triamino-s-triazine / s-Triazine, 2,4,6-triamino- / 1,3,5-Triazine-2,4,6-triamine / Isomelamine	CAS-No.: 108-78-1	1 - 5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: If on skin: Brush off loose particles from skin. . Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. Wash with plenty of water/....
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Dust may cause respiratory tract irritation.
Symptoms/effects after skin contact	: Dust may cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer. Suspected of damaging fertility or the unborn child

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible dust. Products of combustion may include, and are not limited to: oxides of carbon. Toxic fumes. Nitrogen oxides, Phenol, Formaldehyde, oxides of sulphur.
Explosion hazard	: Airborne dust in sufficient concentrations when confined and exposed to a sufficient ignition source can explode.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Use only non-sparking tools.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid generating and breathing dust. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Use only in well ventilated areas. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Use only outdoors or in a well-ventilated area. Formaldehyde is subject to the standard 29 CFR 1910.1048, which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep away from sources of ignition. Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in dust-tight, dry, labelled containers. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Particleboard, laminated or coated

No additional information available

Wood dust, all soft and hard woods (Not applicable)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	1 mg/m ³ (inhalable particles)
---------------	---

USA - OSHA - Occupational Exposure Limits

OSHA PEL TWA [1]	0.75 mg/m ³ (50 mppcf) (Total Dust)
------------------	--

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Wood dust, all soft and hard woods (Not applicable)

USA - NIOSH - Occupational Exposure Limits

NIOSH REL TWA	1 mg/m ³
---------------	---------------------

Melamine (108-78-1)

No additional information available

Urea, polymer with formaldehyde and 1,3,5-triazine-2,4,6-triamine (25036-13-9)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e. there is not leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Lumber.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: May form combustible dust concentrations in air. Capable of catching fire.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: 400 – 500 °F / 204 - 260 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. May form combustible dust concentrations in air.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Avoid dust formation.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Toxic fumes. Nitrogen oxides. Phenol, Formaldehyde, oxides of sulphur.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Melamine (108-78-1)	
LD50 oral rat	3161 mg/kg
LD50 dermal rabbit	> 1 g/kg
LC50 inhalation rat	> 5.19 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Melamine (108-78-1)	
ATE CA (oral)	3161 mg/kg bodyweight

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: May cause cancer.

Wood/Wood dust (Not applicable)

IARC group	1 - Carcinogenic to humans This classification is primarily based on studies showing an association between occupational exposure to wood dust and adenocarcinoma of the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the hypopharynx, oropharynx, lymphatic and hematopoietic systems, lungs, stomach, colon or rectum.
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Melamine (108-78-1)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: Dust may cause respiratory tract irritation.
Symptoms/effects after skin contact	: Dust may cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer. Suspected of damaging fertility or the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	---

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Melamine (108-78-1)	
LC50 - Fish [1]	> 3000 mg/l (Exposure time: 96 h - Species: Poecilia reticulata)
EC50 - Crustacea [1]	> 2000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LOEC (chronic)	> 11 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 11 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 5.1 mg/l Test organisms (species): Pimephales promelas Duration: '36 d'

12.2. Persistence and degradability

Particleboard, laminated or coated	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Particleboard, laminated or coated	
Bioaccumulative potential	Not established.

Melamine (108-78-1)	
BCF - Fish [1]	0.38
Partition coefficient n-octanol/water	1.14 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

No additional information available

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not applicable

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

TDG

Transport hazard class(es) (TDG) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable

Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT

No data available

TDG

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood.

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date : 05/12/2022

Revision date : 05/12/2022

Other information : None..

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Full text of H-statements

Carc. 1A	Carcinogenicity, Category 1A
----------	------------------------------

Particleboard, laminated or coated

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Full text of H-statements	
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Repr. 2	Reproductive toxicity, Category 2

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.