

Medite® II

MDF

MEDFORD, OR

TECHNICAL DATA

Widths*	4 & 5 ft	1.22 & 1.52 m
Lengths*	up to 18 ft	up to 5.49 m
Thicknesses	1/4 - 1-1/2 in	6.35 - 38.10 mm
Density	47 lbs/ft ³	753 kg/m ³
Internal Bond	170 psi	1.17 N/mm ²
Modulus of Rupture/MOR	4,500 psi	31.0 N/mm ²
Modulus of Elasticity/MOE	450,000 psi	3,103 N/mm ²
Hardness/MOH	1,050 lbs	4,671 N
Screw Holding – Face**	300 lbf	1,334 N
Screw Holding – Edge**	250 lbf	1,112 N
Thickness Swell	3.5%	
Linear Expansion	0.25%	
Moisture Content	4 - 6%	
Flame Spread Rating	Class C (3)	
Dimensional Tolerances:		
Length/Width	±0.080 in	±2.0 mm
Squareness	±0.036 in/ft	±3.0 mm/m
Thickness – panel average from specified	±0.005 in	±0.125 mm
Thickness – variance from panel average	±0.005 in	±0.125 mm

Values represent averages for 3/4" panels. Physical properties may vary by thickness. All mechanical properties are tested in accordance with ASTM D1037.

Customer-specified grades are available by request and subject to minimum order quantities.

*Actual length and width panel dimensions are one inch longer than stated size

**Note: panels less than 3/8" are not tested for Screw Holding.

MEDIUM DENSITY FIBERBOARD

MDF panels with improved strength and moisture resistance, made with no added formaldehyde (NAF).

COMMON APPLICATIONS

- Cabinetry and furniture for high-use areas (schools, hospitals, retail, hospitality, museums)
- Wall cladding and wainscot
- Commercial casework and millwork
- Store fixtures
- Stage flooring

Medite® II

MDF

MEDFORD, OR

STANDARDS & CERTIFICATIONS

Roseburg Medite II MDF is tested and certified to meet or exceed the following standards and certifications.

Moisture Resistant

- ✓ Meets grade MR30 moisture resistance

Formaldehyde Emissions Regulations – Third party certified (TPC-1) to meet the requirements of:

- ✓ EPA Formaldehyde Emission Regulation, TSCA Title VI*
- ✓ Standards Council of Canada Formaldehyde Emissions Standard for Composite Wood Products – CAN/CSA 0160-16*
- ✓ California Air Resources Board (CARB) ATCM 93120*
- ✓ No Added Formaldehyde (NAF) Exempt – N-24-313A*

Recycled Content

- ✓ Third-party certified 96.2% pre-consumer recycled content.

Environmental Product Declaration

- ✓ Type III Product Specific EPD Certified by UL Environment

Forest Stewardship Council®

- ✓ Scientific Certification Systems Certified (SCS-COC/CW-00300) – FSC-C017580 FSC® Mix and FSC® Controlled Wood - AVAILABLE OPTION*

Eco-Certified Composite Grademark Program

- ✓ CPA ECC Sustainability Standard*

*Certificates and documentation available at Roseburg.com

GREEN BUILDING SUPPORT:

For LEED® and other green building support documentation, visit roseburg.com/product/medite-ii



3660 Gateway St, Springfield, OR 97477
800.245.1115 | roseburg.com



MEDITE II MEDFORD 111623