

Just the Facts: Armorite® Exterior Trim

Superior strength. Easier handling and finishing. Faster project turnaround. Make Armorite® Exterior Trim part of your next project and get durable, lasting results that both builders and owners love.

SUBSTRATE AND PRODUCT MAKE-UP

- Armorite® Exterior Trim is designed for exterior applications and can be used as an interior trim product, especially in areas with high moisture.
- Armorite® Exterior Trim is a no added formaldehyde (NAF) product, and is not made with urea resins.
- Western softwoods have the physical attributes to withstand weather and handling on the job site.




APPLICATIONS

- Armorite® Exterior Trim can be used for shutters and as fascia for decks, homes, and sheds. Other applications include:
 - Soffits
 - Batten
 - Window Trim
 - Door Trim
 - Frieze Board
 - Belly Band
 - Band Board
 - Corner Board
 - Rake Board
 - Shingle Mold
 - Column Wrap
 - Fluted Door Casing
- In addition to outdoor use, Armorite® Exterior Trim can also be used for high-moisture or humid interior applications.
- Armorite® Exterior Trim is not a structural product.

INSTALLATION AND HANDLING

- Armorite® Exterior Trim adheres to the gap requirements of 1/8" between 16-foot lengths that is industry standard.
- Due to Western softwoods and refining process, Armorite® cuts, machines, and accepts paints better than competitive products.

FASTENER PLACEMENT



SIZE AVAILABILITY

- Armorite® Exterior Trim is available in the most popular sizes.

FINISHES

- Armorite® Exterior Trim is fully reversible and offers textured and smooth modern finishes versus just traditional cedar. Our trim finishes have been well received in the marketplace.

WARRANTY

- Armorite® Exterior Trim warranty is similar to other exterior trim manufacturers in the market today. We offer a 50-year prorated warranty. For the first five years, reimbursement for the cost of replacement product and labor up to 200% of the original purchase price.

THIRD-PARTY TESTING AND CERTIFICATIONS

- Armorite® Exterior Trim is third-party certified to meet ANSI A135.7 Engineered Wood Trim by International Code Council.
- In 2018, Roseburg obtained the Engineering Service Report 4012 certifying Armorite® Exterior Trim meets the ANSI requirements for engineered wood exterior trim.
- A boil test is not a part of the ANSI exterior trim standards.
- Armorite® Exterior Trim resists decay better than competitive products as shown in independent third-party testing.

To learn more, visit roseburg.com/exterior-trim



3660 Gateway St, Springfield, OR 97477
800.245.1115 | roseburg.com



ARMORITE TRIM 103123