

# MDF Moulding



Roseburg is a leading manufacturer of MDF moulding. Our Pembroke facility features state-of-the-art automated moulding lines that produce a variety of popular profiles from our best-in-class MDF panel substrate.

GROWN TO BUILD. BUILT TO GROW.

 **Roseburg**

# MDF Moulding

## TECHNICAL DATA

Roseburg Moulding	
Widths	2" – 7 1/4"
Lengths	7', 8', 12', 14' – 16'
Material	Medium Density Fiberboard
Finish	Smooth double-gesso coated
Profiles	Made-to-order to match current inventory

## INSTRUCTIONS FOR USE

Roseburg MDF Moulding products must be climatized for a period of up to 72 hours prior to installation. During the climatization, the material should be stored on some type of dunnage or 2 x 4s in the areas where the installation will occur. It is important that MDF products are never stored lying directly on a concrete floor, even in a garage. In addition, MDF moulding should never be installed directly to floor surfaces, leave a 3/16" to 1/4" reveal. Click here for complete [installation instructions](#).



## FEATURES AND BENEFITS

Roseburg MDF moldings are primed and require minimal surface preparation for finishing. MDF has a hard surface that will not easily get damaged and will not show raised grain. Our manufacturing process ensures a uniform consistency without the imperfections that may exist in other paint-grade products.

## COMMON APPLICATIONS

- Door Casing
- Baseboard
- Crown Moulding
- Wall Covering
- Chair Rail
- Cased Openings

## STANDARDS & CERTIFICATIONS

- EPA Formaldehyde Emission Regulation, TSCA Title VI compliant
- CPA ECC Sustainability Standard
- 95% pre-consumer recycled content in accordance with ISO 14021 requirements.