



## DuraTemp<sup>®</sup> Exterior Siding Roseburg Forest Products Company

PR-C302

Revised December 19, 2024

Products: DuraTemp Lap and Panel Siding

Roseburg Forest Products Company, Post Office Box 1088, Roseburg, Oregon 97470

(541) 679-3311

[www.roseburg.com](http://www.roseburg.com)

### 1. Basis of the product report:

- 2024 International Building Code (IBC): Sections 104.2.3 Alternative materials and 2303.1.5 Wood structural panels
- 2021, 2018 and 2015 IBC: Sections 104.11 Alternative materials and 2303.1.5 Wood structural panels
- 2024 International Residential Code (IRC): Sections R104.2.2 Alternative materials, and R604 Wood structural panels
- 2021, 2018, and 2015 IRC: Sections R104.11 Alternative materials and R604 Wood structural panels
- 2022 California Building Code (CBC): Sections 104.11 Alternative materials and 2303.1.5 Wood structural panels
- 2022 California Residential Code (CRC): Sections R104.11 Alternative materials and R604 Wood structural panels
- 2021 and 2015 ANSI/AWC SDPWS, Special Design Provisions for Wind and Seismic, recognized in the 2024, 2021 IBC, and 2022 CBC, and 2018 and 2015 IBC, respectively
- 2019, 2014, and 2008 ANSI/APA PRP 210, Standard for Performance-Rated Engineered Wood Siding, recognized in the 2024 and 2021 IBC and IRC and 2022 CBC and CRC, 2018 IBC and IRC, and 2015 IBC and IRC, respectively
- 2021 APA PRP-108, Performance Standards and Qualification Policy for Wood Structural Panels
- APA Reports R&D 89Q-25, T95Q-12, and T2009Q-27, and other qualification data

### 2. Product description:

Roseburg DuraTemp exterior siding is made with a plywood base panel and a hardboard face in accordance with the specifications listed in the plant Quality Control Manual. It is available as panel siding and as lap siding, and has shiplap or square edges. Table 1 lists Roseburg DuraTemp performance categories and span ratings.

### 3. Design properties:

Shear wall values for Roseburg DuraTemp panel siding are the same as for plywood siding as listed in Tables 4.3A and 4.3B of the 2021 and 2015 SDPWS. Bracing requirements as listed in Table R602.10.4 of the 2024, 2021, 2018, and 2015, and 2022 CRC for wood structural panels are applicable to Roseburg DuraTemp panel siding. Nailing requirements for Roseburg DuraTemp panel siding are in accordance with Table 2304.10.2 of the 2024 and 2021 IBC and 2022 CBC, Table 2304.10.1 of the 2018 and 2015 IBC, and Table R602.3(1) of the 2024, 2021, 2018, and 2015 IRC and 2022 CRC. Roseburg DuraTemp panel siding satisfies the requirements of Table R703.3(1) of the 2024, 2021, 2018, and 2015 IRC, and 2022 CRC as an exterior wall covering.

### 4. Product installation:

Roseburg DuraTemp siding shall be installed in accordance with the recommendations provided by the manufacturer ([www.roseburg.com](http://www.roseburg.com)) and APA Design/Construction Guide: *Engineered Wood Construction Guide*, Form E30 ([www.apawood.org/resource-library](http://www.apawood.org/resource-library)). The maximum span shall be in accordance with the Span Rating shown in the trademark.

5. Fire-resistant construction:  
 Untreated wood structural panels have been shown to meet a Class III (or C) category for flame spread. Unless otherwise specified, fire-resistant construction shall be in accordance with APA Design/Construction Guide: *Fire-Rated Systems*, Form W305 (see link above).
  
6. Limitations:
  - a) Roseburg DuraTemp lap siding is not recognized for shear wall applications except when applied over nailable sheathing or other code-recognized provisions.
  - b) Roseburg DuraTemp lap or panel siding used outdoors must be finished in accordance with recommendations provided by the manufacturer (see link above) and APA Design/Construction Guide: *Engineered Wood Construction Guide*, Form E30 (see link above).
  - c) Roseburg DuraTemp siding is produced at Roseburg Forest Products Company facilities in Dillard and Riddle, OR under a quality assurance program audited by APA.
  - d) This report is subject to re-examination in one year.
  
7. Identification:  
 Roseburg DuraTemp siding described in this report is identified by a label bearing the manufacturer's name (Roseburg Forest Products Company) and/or trademark, the product performance category, the Span Rating, the Exposure Rating, the APA assigned plant number (480 for Dillard, OR, and 482 for Riddle, OR), the APA logo, the report number PR-C302, and a means of identifying the date of manufacture.

Table 1. Product Performance Categories and Span Ratings

Product	Performance Category	Span Rating <sup>(a)</sup>
Lap Siding	1/2	24 o.c.
Panel Siding	3/8	16 o.c.
	13/32	16 o.c.
	15/32	16 o.c. or 24 o.c.
	1/2	16 o.c. or 24 o.c.
	19/32	16 o.c. or 24 o.c.

<sup>(a)</sup> The Span Rating for Roseburg DuraTemp siding panels in these performance categories may vary, depending on the panel construction details and is identified in the trademark.

APA – *The Engineered Wood Association* is an approved national standards developer accredited by American National Standards Institute (ANSI). APA publishes ANSI standards and Voluntary Product Standards for wood structural panels and engineered wood products. APA is an accredited certification body under ISO/IEC 17065 by Standards Council of Canada (SCC), an accredited inspection agency under ISO/IEC 17020 by ANSI National Accreditation Board (ANAB), and an accredited testing organization under ISO/IEC 17025 by ANAB. APA is also an approved Product Certification Agency, Testing Laboratory, Quality Assurance Entity, Validation Entity, and Product Evaluation Entity by the State of Florida, and an approved testing laboratory by City of Los Angeles.

**APA – THE ENGINEERED WOOD ASSOCIATION  
HEADQUARTERS**

7011 So. 19<sup>th</sup> St. • Tacoma, Washington 98466  
Phone: (253) 565-6600 • Fax: (253) 565-7265 • Internet Address: [www.apawood.org](http://www.apawood.org)

**PRODUCT SUPPORT HELP DESK**  
(253) 620-7400 • *E-mail Address:* [help@apawood.org](mailto:help@apawood.org)

**DISCLAIMER**

APA Product Report® is a trademark of APA – *The Engineered Wood Association*, Tacoma, Washington. The information contained herein is based on the product evaluation in accordance with the references noted in this report. No warranties, express or implied, including as to fitness for a particular purpose, are made regarding this report. Neither APA nor its members shall be liable, or assume any legal liability or responsibility, for damages, direct or indirect, arising from the use, application of, and/or reference to opinions, findings, conclusions or recommendations included in this report. Consult your local jurisdiction or design professional to assure compliance with code, construction, and performance requirements. Because APA has no control over quality of workmanship or the conditions under which engineered wood products are used, it cannot accept responsibility for product performance or designs as actually constructed.